

IEEE 802.11g (54Mbps) mini PCI Wireless LAN Module

Zcomax Technologies, Inc. has released its new line of Air Runner™ wireless LAN mini-PCI cards. The XG-623H+ is an IEEE 802.11g 54Mbps mini PCI module that has been designed with the integration market in mind. With its low profile external antenna connector and standard mini PCI form, the XG-623H+ will fit into any design that supports the mini-PCI form factor. The XG-623H is a high performance module that exceeds both IEEE 802.11g and FCC regulatory requirements.



The XG-623H+'s reliable design helps to reduce overall costs associated with wireless integration by eliminating the need for debugging and driver support commonly associated with designing a product from the "ground up". The XG-623H+ module is a robust plug and play ready device that has support for both windows and Linux operating systems.

With an excellent price / performance ratio and the field-proven reliability associated with the Atheros chipset, the XG-623H+ is a superb choice for any wireless application requiring enhanced connectivity and reliability.

XG-623H+ at a glance

- IEEE 802.11g compliant
- 24dBm Tx output Power
- -72Bm @ 54Mbps Rx Sensitivity
- 2 Hirose U.FL Antenna Connector
- FCC and ROHS compliant
- Chipset – Atheros AR2413
(Single Chip Design)
- Driver support – Windows, Linux and customized drivers are available.



Table of Contents

	<i>Page</i>
<i>Physical Specification</i>	3
<i>RF Specification</i>	3
<i>Electrical Specification</i>	4
<i>Antenna Connector Specification</i>	4
<i>Environmental</i>	4
<i>Absolute Maximum Rating</i>	4
<i>Performance</i>	5
<i>Security</i>	5
<i>Reliability</i>	5
<i>Interoperability</i>	5
<i>Warranty</i>	5

Physical Specification:

Form Factor	32-bit Mini PCI, Type III B
Dimensions (L x W x H)	59.6mm(L) * 44.5mm(W) * 2.7mm (H)
Weight	≤ 50 g

RF Specification:

Frequency Range (GHz)	North America:
	FCC: 2.412 ~ 2.462GHz (CH1 ~ CH 11)
	TELEC: 2.412~2.472GHz (CH1 ~ CH 13)
	ETSI: 2.412 ~ 2.472GHz (CH1 ~ CH 13)
Frequency Drift	<25KHz
Transmitter Output Power	
IEEE 802.11g 54Mbps	24dBm ± 1dBm
IEEE 802.11b 11 Mbps	23dBm ± 1dBm
Antenna Impedance	50 ohms
Media Access Protocol	CSMA/CA w/ACK
802.11g Data rates	54, 48, 36, 24, 12, 9, 6 Mbps
Modulation	48/54 Mbps (QAM-64) 24/36 Mbps (QAM-16) 12/18 Mbps (QPSK) 6/9 Mbps (BPSK)
Receiver Sensitivity @ PER < 10% for 802.11g	54 / 48 Mbps: ≤ -72dBm / -75dBm
	36 / 24 Mbps: ≤ -78dBm / -82dBm
	18 / 12 Mbps: ≤ -84dBm / -86dBm
	9 / 6 Mbps: ≤ -88dBm / -90dBm
Receiver Sensitivity @ PER < 8% for 802.11b	11 / 5.5 Mbps: ≤ -87dBm / -88dBm
	2 / 1 Mbps: ≤ -90dBm / -92dBm

Electrical Specification:

Supply Voltage	3.3 Vdc, +/- 5%
Supply Voltage Ripple	120mV (pp) max.
Power-on startup time	<600 ms
Sleep-to-receive startup time	<75 ms
Power consumption	TX: < 1.5A, RX: < NA,

Antenna Connector Specification

Connector Type	1 x Hirose U.FL 50Ω
Manufacturer	Hirose Electronic Co. Ltd.
Part Number	U.FL-R-SMT (CL331-0471-0-01)

Environmental

Working Temperature	0 ~ 55°C, 90% relative humidity (non-condensing)
Storage Temperature	-20 ~ 80°C, 90% relative humidity (non-condensing)

Absolute Maximum Rating

Stress above those listed in Absolute Maximum Rating may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in standard specifications is not implied.

Supply Voltage	3.7V
I/O Voltage	-0.5V ~ VCC+0.3V
Storage Temperature	-20 ~ +80°C, 95% relative humidity (non-condensing)
Barometric Pressure	740 hPa ~ 1050 hPa

Performance

The range of a RF subsystem is determined by many different factors, including antenna design and cable loss, as well as connector selection. Typical ranges are given for PER < 10% (802.11g) and assume an adequate antenna design.

Open Space – 802.11g	60 meters @ 54 Mbps
Open Space – 802.11g	120 meters @ 24/18 Mbps
Open Space – 802.11g	120 meters @ 12/9/6 Mbps
Open Space – 802.11b	80 meters @ 11 Mbps
Open Space – 802.11b	300 meters @ 1Mbps

Security

The XG-623H+ supports WPA / WPA2 and IEEE 802.1X. Support will be equal to or greater than the latest Atheros supplied driver.

Reliability

Mean Time To Failure is rated at 150,000 hours.

Interoperability

The XG-623H+ interoperates with any IEEE 802.11g compliant devices.

Warranty

The XG-623H+ is supplied with a 12 month warrantee against manufacturing defects.